

## AMENDMENTS TO THE CLAIMS

The following listing of claims replaces all prior versions, and listings, of claims in the captioned patent application:

### **Listing of Claims:**

1. (Currently Amended) An electrically conducting lead comprising:
  - a- ~~a substantially electrically-insulative elongate body of relatively electrically insulative material; and~~
  - ~~a relatively~~ an electrically conductive element, wound around a length of said elongate body, having first and second ends, and comprising a plurality of layers each comprising a plurality of electrical conductors extending through at least a portion of said insulative body in a wound arrangement, wherein positioned within said conductive element such that each of said conductors at the first end are correspondingly identifiable at said second end. ~~said electrically conductive element comprises a plurality of layers of electrical conductors with the longitudinal extent of each of said electrical conductors over said portion of the lead being substantially identical.~~
2. (Original) The electrically conducting lead of claim 1 wherein the wound arrangement of the electrically conductive element is a helically wound arrangement.
3. (Original) The electrically conducting lead of claim 1 wherein the electrically conductive element extends from a first end to a second end of the lead.
4. (Original) The electrically conducting lead of claim 3 wherein the longitudinal extent of each of said electrical conductors over the length of the lead from the first end to the second end is substantially identical.
5. (Original) The electrically conducting lead of claim 4 wherein the longitudinal extent of the electrical conductors over the length of the lead from the first end to the second end is identical.

6. (Currently Amended) The electrically conducting lead of claim 1 wherein the electrically conductive element configured to extend ~~extending~~ through said portion of the insulative body is wound in an anticlockwise direction for a length of said portion and in a clockwise direction for a length of said portion, ~~if looking at the lead from one of the ends of the lead.~~

7. (Original) The electrically conducting lead of claim 6 wherein the length of the conductive element that is wound in an anticlockwise manner is substantially equal to the length of the conductive element that is wound in a clockwise manner.

8. (Original) The electrically conducting lead of claim 7 wherein the length of the conductive element that is wound in an anticlockwise manner is equal to the length of the conductive element that is wound in a clockwise manner.

9. (Original) The electrically conducting lead of claim 7 wherein at the transition from anticlockwise to clockwise windings, the conductive element is folded back on itself.

10. (Original) The electrically conducting lead of claim 1 wherein the conductive element is wound in one direction for the length of said portion of the insulative body and further wherein the layer is twisted by 180.degree. at a location along the length of the body.

11. (Original) The electrically conducting lead of claim 10 wherein the twist is at a midway point of the length of the wound conductive element in the lead.

12. (Original) The electrically conducting lead of claim 1 wherein each layer of the conductive element is comprised of a plurality of separate electrical conductors, with each layer having the same number of conductors as the other layers in the element.

13. (Original) The electrically conducting lead of claim 1 wherein each layer of the conductive element is comprised of a plurality of separate electrical conductors, with the number of conductors of at least one of the layers varying from the number in one, more or all of the other layers of the element.

14. (Original) The electrically conducting lead of claim 1 wherein the electrical conductors are made of platinum.

15-23. (Cancelled)

24. (Currently Amended) An electrically conducting lead comprising:

~~a body of relatively substantially electrically insulative material elongate body; and~~  
~~a relatively an electrically conductive element, wound around a length of said elongate~~  
~~body, having first and second ends, and comprising a plurality of layers each comprising a~~  
~~plurality of electrical conductors, extending through at least a portion of said insulative body in a~~  
~~wound arrangement;~~

~~wherein said electrically conductive element comprises a plurality of layers of electrical~~  
~~conductors with the number of conductors of at least one of the layers varies in number varying~~  
~~from the number of conductors in at least one of the other layers of the element, and further~~  
~~wherein said plurality of electrical conductors are positioned within said conductive element~~  
~~such that each of said conductors at the first end are correspondingly identifiable at said second~~  
~~end.~~

25. (Original) The electrically conducting lead of claim 24 wherein the number of conductors in said one of the layers varies from the number in more than one of the other layers of the element.

26. (Currently Amended) An electrically conducting lead comprising:

~~a body of relatively substantially electrically insulative material electrically-insulative elongate body; and~~

~~a relatively an electrically conductive element extending through at least a portion helically wound around a length of said insulative elongate having first and second ends-body in a helically wound arrangement;, and comprising a plurality of layers each comprising a plurality of electrical conductors positioned within said conductive element such that wherein said electrically conductive element comprises a plurality of layers of electrical conductors, with each layer of electrical conductors being made up of a plurality of separate electrical conductors, with the position of each of said plurality of electrical conductors comprising each layer electrical conductor being constant with regard respect to said plurality of electrical conductors of neighbouring layers its neighbour and the position of each layer of electrical conductors being constant with regard to its neighbouring layer over the length of said portion of said insulative body remain constant between said first and said second ends of said insulative body, and further wherein each of said plurality of electrical conductors are positioned such that each of said conductors at the first end are correspondingly identifiable at said second end.~~

27-28. (Cancelled)

29. (New) The electrically conducting lead of claim 7 wherein with the longitudinal extent of each of said electrical conductors over said portion of the lead are substantially identical when in said wound arrangement.